

# #10 Panclip XLP Econo Fastener



A new addition to the XLP line for those customers who love the XLP fastener line but do not need the extra corrosion resistance that the DMG85 coated XLP fasteners provide. The Panclip XLP Econo fastener

## Features:

- Panclip XLP Extra Low profile pancake/wafer head popular for Nail Strip panel installation reducing head marks you might find with a taller pancake head.
- A versatile #2 square drive / #2 phillips drive combination.
- Zinc Plated
- Sharp or TP-17 Point

## Specifications

#10-9 x (L) SQ2/PH2 TP-17 Point  
C1022 Carbon Steel  
White Electro Plated Zinc 0.003

#10-8 x (L) SQ2/PH2 Sharp Point  
C1022 Carbon Steel  
White Electro Plated Zinc 0.003

#10-8 Thread Diameter: Maj: .202" Min .132"  
Head Height .038" - .042"  
Head Diameter: .428" - .445"

Tensile Strength: 1,800 lbs ult

Torsional: 60 in-lbs

Shear: 1,426 lbs ult

Pull out :

Southern Yellow Pine: 525 lbs ult

Values may change with strength and condition of substrate wood.

COO: Manufactured in China (PRC)



## Selection

Econo Zinc Plated Only, PH2/SQ2,

<u>Available Sizes</u>	<u>Qty/Box</u>	<u>Part#</u>
#10-8 x 1"	5,000	DMIPX10100CH
#10-9 x 1"	5,000	DMIPX10102TSPC

## Installation

SQ2 or PH2 driver tip suggested.

0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.

Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Suggested full 1" penetration into substrate.

## Limitations

Not for use in areas within 3000 Inft of salt or brackish water, or coastal areas. Not for use in the State of Florida or other areas subject to Florida Building Code or Miami-Dade Product Control.

Not for use on or with Aluminum or Copper roofing panels or clips.