

## WELDABLE ONE WAY TPO VENTS

EX-Flow one way TPO vents  
Strong UV stabilized White TPO one way vents  
with locking, vandal proof cap prevents entry of  
wind blown rain. Part # BV-1095  
8" height, 5-1/4" Base Opening, 10-1/2"

- Weld directly to TPO membrane
- Fast installation
- No adhesive or sealant needed
- 100% UV protected
- Inexpensive
- Ventilates cores
- Made in the U.S.A.



## TERMINATION BAR

The DEK-ZIP TERM BAR for edge or vertical parapet wall terminations.

- 6063-T6 ALUMINUM CONSTRUCTION FOR CORROSION RESISTANCE
- INTEGRAL REINFORCEMENT RIBS
- 6" ON CENTER FASTENER HOLES
- 10' LONG PIECES, 50 PIECES/TUBE
- USE WITH #12, #14 OR #15 FASTENERS
- SEALANT LEDGE "LIP" BAR AVAILABLE
- FLAT BAR AVAILABLE



### Term Bar Selection Guide

Size	Part#	Quantity/Tube
Flat	DMI9RTBF10A	500 Inft / 50 pcs
Lip / Ledge	DMI9RTBK10A	500 Inft / 50 pcs

## SCREWS & PLATES

The #15-13 DEK-ZIP fastener is designed for insulation or membrane attachment to wood, concrete and light gauge metal decking.

- 18 LENGTHS AVAILABLE FROM 1-1/4" - 24"
- PRECISION SD#1 DRILL POINT
- BLACK EPOXY 1000 HR COATING, CORROSION RESISTANT TO FM 4470 STANDARD ASTM D6294, DIN50018 SFW2.0S.
- COMPATIBLE WITH STANDARD SEAM AND STRESS PLATES
- PACKAGED IN JOBSITE FRIENDLY RE-SEALABLE PLASTIC PAILS
- PHILLIPS #3 DRIVE



### BARBED SEAM PLATES

The DEK-ZIP barbed galvalume seam plate is designed for membrane attachment to wood, steel or cover-board.

- AZ50 GALVALUME CONSTRUCTION FOR CORROSION RESISTANCE
- 22GA GALVALUME
- 2-3/8" DIAMETER
- MULTIPLE RIB DESIGN FOR STRENGTH
- RECESSED FASTENER HOLE FOR LOW PROFILE
- USE WITH #12, #14 OR #15 FASTENERS
- PACKAGED IN JOBSITE FRIENDLY RE-SEALABLE PLASTIC PAILS



### Working to exceed expectations

If you need assistance in selecting the correct product for your project, please call our office to talk with a product specialist please call 855-800-8878.

**D.M.I. products are distributed by:**

[www.directmetalsinc.com](http://www.directmetalsinc.com)



## TPO MEMBRANE ROOFING ACCESSORIES

## WELDABLE GOOSENECK VENTS, RETROFIT DRAINS, PIPE FLASHINGS, ONE WAY VENTS



## WELDABLE TPO PIPE FLASHINGS

*The* Bullet Products solution for TPO flat roofing pipe penetrations. This flashing is made with white Polyolefin Elastomer (TPO) and can quickly be heat welded to TPO roofing systems. The internal design improves water tightness with no caulking needed for installation. The boot is designed to be an aesthetically pleasing and features a removable pest screen.

Available in sizes to fit : 1-1/2", 2", 3" & 4" Pipes



### Features & Benefits

- Fast installation, no painting needed
- Covers the pipe inside and out
- Weldable 80mil flange
- No sealant needed
- Very Affordable
- 35 Year limited factory warranty
- Non staining , lead free TPO
- Built-in UV protection
- Made in the U.S.A.

### Common Applications

- Iron or PVC Pipe Roof Penetrations

## WELDABLE TPO GOOSENECK VENTS

*The* Bullet Products solution for TPO flat roofing vent and wire penetrations. This flashing is made with white Polyolefin Elastomer (TPO) base that can quickly be heat welded to TPO roofing systems. Quick and easy installation with no sealants or curbs needed. Aesthetically pleasing, oil resistant and features a removable pest screen and damper.

20" x 19" Weldable TPO base, 12-1/4" height , Intake 8" above deck with a 9-1/2" x 10" throat.



### Features & Benefits

- Fast installation, no painting needed
- Weldable 80mil flange
- Colored throughout
- 100% UV protected, removable top
- Very Affordable
- 35 Year limited factory warranty
- Removable pest screen & damper
- Made in the U.S.A.

### Common Applications

- Dryer, kitchen, or fan exhausts
- Wire sets
- General ventilation

## WELDABLE TPO RETROFIT DRAINS

The Aluminator Retrofit Roof Drain is now available with a TPO coated flange for quick and easy installation in TPO membrane roof systems. All aluminum construction with a strong mechanical proseal to prevent water backflow issues. Certified to conform with ASME 112.6.4 and CSA B79 standards.

Available in sizes: 2", 3", 4", 5", 6" and 8"



### Features & Benefits

- TPO coated flange
- All heavy gauge spun Aluminum construction
- HD cast aluminum ring designed for max drainage
- Cast aluminum strainer
- Proseal to prevent water back-up issues
- Made in the U.S.A.

