

End cap flashings For profile end termination




Designed to waterproof end terminations on popular metal roof panels

Sleeve flexibility to absorb vibration and movement caused by expansion/contraction while sealing out unwanted elements. Specifically molded for 3/4" tall rib profile, R/PBR profiles or trapezoidal metal panels. Available in standard Grey EPDM rubber.

- Superior sleeve flexibility and vibration resistant.
- Aluminum base ring for easy molding and fastener stability.
- 20 Year limited warranty and superior weatherability.



RCAP



RIBCAP



MC1

Specifications

Performance Temperature Range

Standard EPDM flashings -65 deg F to 212 deg F

Adv Ozone Resistance Testing: 70 hr @ 500pphm

RIBCAP 7/8" overall height x inner wall width of 2" inner depth/length of 2-3/4"

RCAP 1-1/2" overall height x inner wall width of 3-1/2" inner depth/length of 4-1/2"

MC1 3-1/4" overall height x inner wall width of 3" inner depth/length of 1-1/2"



Made in Mexico,

Packaged in the U.S.A.

Selection



RIBCAP GRAY EPDM

Size Fits	Base	Qty/Box	Part# / Part#
3/4" RIB PANEL	3.25" x 2.5"	10	DMRIBCAP/MC051GA



RIBCAP GRAY EPDM

Size Fits	Base	Qty/Box	Part#
R/PBR PANEL	5.50" x 5.0"	10	DMPBRCAP



MC1 GRAY EPDM

Size Fits	Base	Qty/Box	Part#
2.5-3.0 TRP	4.00" x 2.0"	5	MC101BA

Installation

Ask for installation guide

MSDS: Based on current requirements of the occupational safety and health administration code, 26CFR, part 19101200 (Hazard communication), it has been determined that our pipe flashing products are considered "articles". A material safety data sheet is not required for items meeting the code definition of "article".

To find a distributor of DMI DIRECT METALS products please visit www.directmetalsinc.com or call 855-800-8878